

DESCRIPTION

Spray Wash is a high strength, alkaline, foaming liquid detergent designed for touchless automatic car wash systems. It is applied at low pressure through the spray arch mechanism in a touchless car wash to penetrate the dirt and road film to be removed by the pressure rinse cycle of the wash. **Spray Wash** is for soft to medium water hardness conditions.

FEATURES & BENEFITS

economical to use • high dilution ratio • high foaming • highly alkaline • designed for touchless car wash • soft to medium water hardness

DIRECTIONS

Apply **Spray Wash** at a rate of 3-4% at 40-50°C in soft water conditions (slightly more may be required in hard water). A 30 second contact time is recommended for best results. Pressure rinse at 1000 p.s.i. or more with clean hot water. Hot or cold wax should be applied prior to drying.

FIRST AID

Eyes & Skin: If eye or skin contact occurs, immediately flush with plenty of water for at least 15 minutes. Call a physician. **Inhalation:** Remove to fresh air. Call a physician. **Ingestion:** If swallowed, promptly give plenty of water or milk. Do not induce vomiting. Call a physician.

For further information, please review the **Safety Data Sheet (SDS)** and **Product Label**.

STORAGE & HANDLING

Keep from freezing. Store upright in original closed container at room temperature away from children. Do not mix with any other chemicals.

Do not store in aluminum, copper, copper alloys and galvanized containers.

PHYSICAL DATA

Package: 18.9L pails, 208L drums & 113L drums

Appearance: liquid

Colour: blue

Foam: high

Odour: odourless

pH: alkaline

ProjectClean.com

1607 Derwent Way, Delta, BC, Canada V3M 6K8
1-800-663-9925

Product codes:

1401405-18.9

1401405-208

1401405-113l