

Safety Data Sheet Sections

SECTION 1: IDENTIFICATION	2
SECTION 2: HAZARD IDENTIFICATION	2
PRECAUTIONARY STATEMENTS	2
SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS	3
SECTION 4: FIRST-AID MEASURES	3
SECTION 5: FIRE-FIGHTING MEASURES	4
SECTION 6: ACCIDENTAL RELEASE MEASURES	5
SECTION 7: HANDLING AND STORAGE	5
SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION	5
EXPOSURE LIMITS:	5
INDIVIDUAL PROTECTION MEASURES / PERSONAL PROTECTIVE EQUIPMENT	5
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES	ε
SECTION 10: STABILITY AND REACTIVITY	7
SECTION 11: TOXICOLOGICAL INFORMATION	7
SECTION 12: ECOLOGICAL INFORMATION	7
SECTION 13: DISPOSAL CONSIDERATIONS	8
SECTION 14: TRANSPORT INFORMATION	8
SECTION 15: REGULATORY INFORMATION	8
SECTION 16: OTHER INFORMATION	g
ACRONYM LIST	c

SECTION 1: IDENTIFICATION		
Product Trade Name:	Maxim P.O.G. Non-volatile Spotter	
Product Code:	1300875	
Recommended Use:	Water based carpet spotter	
Restrictions on Use:	For Industrial and Institutional use only	
Manufacturer Name:	Project Clean Inc.	
Manufacturer Address:	1607 Derwent Way, Delta, B.C. Canada V3M 6K8	
Manufacturer Phone Number:	800-663-9925	
Email Address of Competent Person Responsible for the SDS:	regulatory@projectclean.com	
Emergency Phone Number/ 24-Hour Number:	For Transportation Emergencies: Canutec 613-996-6666 Emergency Response Services: Chemtrec 800-424-9300	

SECTION 2: HAZARD IDENTIFICATION		
Physical Hazards:	NONE	
Health Hazards:	SKIN CORROSION/IRRITATION – Category 2	
	EYE DAMAGE/IRRITATION – Category 1	
	ASPIRATION HAZARD – Category 1	
Symbol:		
Signal word:	DANGER	
Hazard Statement:	H315 Causes skin irritation.	
	H318 Causes serious eye damage.	
	H304 May be fatal if swallowed and enters airways.	
PRECAUTIONARY STATEMENTS		
Prevention:	P264 Wash hands or affected area thoroughly after handling.	
	P280 Wear protective gloves/protective clothing/eye protection/face protection.	
Responses:	P305 + P354 + P338 + P317 IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help.	

SECTION 2: HAZARD IDENTIFICATION		
	P302 + P352 + P332 + P317 + P362 + P364 IF ON SKIN: Wash with plenty water. If skin irritation occurs: Get medical help. Wash contaminated clothing before reuse.	
P301 + P316 + 331IF SWALLOWED: Get emergency medical help immediately. Do NOT induce vomiting.		
	P321 Specific treatment (see supplemental first aid information on this label).	
Storage:	P405 Store locked up.	
Disposal:	P501 Dispose of contents/ container to an approved waste disposal plant.	

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS		
Ingredient	Approx. Wt.%	CAS Number
Alcohol Ethoxylate	10-30	68439-46-3
2-Butoxyethanol	5-10	111-76-2
Alcohol Ethoxylate	1-5	68991-48-0
Isopropanol	1-5	67-63-0

Back to Top

SECTION 4: FIRST-AID MEASURES		
General Information:	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.	
Inhalation:	Immediately remove the affected victim to fresh air. If symptoms persist, obtain medical attention. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if feeling unwell.	
Skin Contact:	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.	
Eye Contact:	Immediately flush with warm running water for at least 15 minutes, holding eyelids open during flushing. Remove contact lenses, if present and easy to do. If irritation persists, repeat flushing and obtain medical attention immediately.	
Ingestion:	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.	

PREPARED BY:
Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE: 2020-07-06

SECTION 4: FIRST-AID MEASURES		
Self-Protection of the First Aider:	Remove all sources of ignition. Ensure that first aid personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.	
Most Important Symptoms/ Effects, Acute and Delayed:	Ingestion: Small amounts swallowed incidental to normal handling operations are not likely to cause injury. May burn mouth and throat. Inhalation: Low toxicity. Eyes and skin: May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Brief contact may cause skin burns.	
Note to Physicians:	Treatment based on sound judgment of physician and individual reactions of patient. Due to structural analogy and clinical data, this material may have a mechanism of intoxication similar to ethylene glycol. On that basis, treatment similar to ethylene glycol intoxication may be of benefit. In cases where several ounces (60 - 100 ml) have been ingested, consider the use of ethanol and hemodialysis in the treatment. Consult standard literature for details of treatment. If ethanol is used, a therapeutically effective blood concentration in the range of 100 - 150 mg/di may be achieved by a rapid loading dose followed by a continuous intravenous infusion. Consult standard literature for details of treatment. 4-Methyl pyrazole (Antizol®) is an effective blocker of alcohol dehydrogenase and should be used in the treatment of ethylene glycol (EG, di- or triethylene glycol (DEG, TEG), ethylene glycol butyl ether (EGBE), or methanol intoxication if available. Fomepizole protocol (Brent, J. et al., New England Journal of Medicine, Feb. 8, 2001, 344:6, p. 424-9): loading dose 15 mg/kg intravenously, follow by bolus dose of 10 mg/kg every 12 hours; after 48 hours, increase bolus dose to 15 mg/kg every 12 hours. Continue fomepizole until serum methanol, EG, DEG, TEG or EGBE are undetectable. The signs and symptoms of poisoning include anion gap metabolic acidosis, CNS depression, renal tubular injury, and possible late stage cranial nerve involvement. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Maintain adequate ventilation and oxygenation of the patient. In severe poisoning, respiratory support with mechanical ventilation and positive end expiratory pressure may be required. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control	
If irritation occurs or persists, get medical attention.		

SECTION 5: FIRE-FIGHTING MEASURES		
Suitable Extinguishing Media: Water fog, alcohol foam, dry chemical.		

SECTION 5: FIRE-FIGHTING MEASURES		
Unsuitable Extinguishing Media:	Direct water stream.	
Flammability:	Not flammable.	
Flash Point:	Not flammable.	
Special Firefighting Procedures:	Wear NIOSH/MSHA approved, self-contained breathing apparatus for firefighting situation. Use water spray to cool all nearby fire exposed surfaces.	
Unusual Fire / Explosion Hazards:	Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.	
Hazardous Decomposition Products:	Oxides of sodium, carbon, and other unidentifiable organic compounds.	

SECTION 6: ACCIDENTAL RELEASE MEASURES		
Environmental Protection Precautions:	Do not release to the environment or water source.	
Steps to be Taken in Case Material is Released or Spilled:	Wear protective equipment. Soak up spills with absorbents, then dispose of in an appropriate waste container. Keep material away from sewers. Reuse if possible. Otherwise dispose recovered material in accordance with all local, Provincial or Federal regulations.	

Back to Top

SECTION 7: HANDLING AND STORAGE		
Precautions to be Taken in Handling and Storage:	Use good industrial hygiene. Do not get in eyes. Avoid contact with skin and clothing. Avoid breathing sprays or mists. Store in a cool, dry place away from incompatibles. Keep container closed when not in use. Do not mix with any other chemicals. Store at temperatures below 30oC (86oF) and keep from freezing. Do not store in aluminum, copper, copper alloys and galvanized containers.	

Back to Top

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION		
EXPOSURE LIMITS:		
OSHA (PEL): N/A	ACGIH TLV: N/A	Other exposure limit: N/A
INDIVIDUAL PROTECTION MEASURES / PERSONAL PROTECTIVE EQUIPMENT		
Appropriate Engineering Controls:	Mechanical or good general ventilation.	
Skin Protection:	Butyl rubber, neoprene, latex or nitrile gloves. Personal protective equipment for the body should be selected based on the task being	

PREPARED BY:
Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION	
	performed and the risks involved. Appropriate footwear should be selected based on the task being performed and the risks involved.
Eye and Face Protection:	Safety glasses or chemical goggles. Face shield if splashing hazard exists.
Respiratory Protection:	Good general ventilation or local exhaust ventilation for spraying and misting in confined areas.
Other Protective Equipment:	Eye wash, safety shower and full protective clothing recommended in the immediate work area. Rubber boots.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES	
Appearance:	Clear, colourless liquid.
Odour:	Banana.
Odour threshold:	N/A
pH:	8-9
Melting point/Freezing point:	N/A
Initial boiling point and boiling range:	N/A
Flash Point:	> 100°C
Evaporation Rate (Water=1):	N/A
Flammability:	Not flammable
Upper/Lower flammability or explosive limits:	None
Vapour pressure:	N/A
Vapour density:	N/A
Relative density/Specific gravity (Water = 1):	1.00 @ 20 °C
Solubility(ies):	Soluble in water
Partition coefficient: n-octanol/water:	N/A
Auto-ignition temperature:	Not flammable
Decomposition temperature:	N/A
Viscosity:	Thin like water.
VOCs:	N/A

Back to Top

SECTION 10: STABILITY AND REACTIVITY	
Reactivity:	N/A
Chemical stability:	Stable under normal storage conditions.
Possibility of hazardous reactions:	Avoid contact with acid/oxidizers.
Conditions to avoid:	Temperatures above 30°C and below 5°C. Avoid contact with incompatible materials.
Incompatibility:	Metals such as aluminum, brass, copper. Nitrites, strong acids, halogenated hydrocarbons.
Hazardous Decomposition Products:	Oxides of sodium, carbon, and other unidentifiable organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION		
Likely routes of exposure:	Ingestion, skin and eye contact.	
Symptoms:	Corrosive to eyes and skin.	
Acute Toxicity Estimates:	LD ₅₀ Oral ATE > 2000 mg/kg	
	LD ₅₀ Dermal ATE > 2000 mg/kg	
	LD ₅₀ Inhalation ATE: N/A	
Skin Sensitization:	Data available on components indicates no potential skin sensitization.	
Germinal Cell Mutagenicity:	Data available on components indicates no potential germinal cell mutagenicity.	
Reproductive Toxicity:	Data available on components indicates no potential reproductive toxicity.	
Carcinogenicity:	Not listed by NTP, IARC, OSHA, ACGIH.	
Aspiration Hazard:	8% of the components are classified as aspiration hazard.	

Back to Top

SECTION 12: ECOLOGICAL INFORMATION	
Toxicity to Fresh Water Algae:	Alcohol Ethoxylate (CAS# 68439-46-3):
,	EC ₅₀ (algae)
	10-100 mg/L, Exposure Time: 72 h, Test Type: N/A
Toxicity to Fish Species:	Alcohol Ethoxylate (CAS# 68439-46-3):
, ,	LC ₅₀ (fish)
	5-10 mg/L, Exposure Time, 96 h, Test Type: N/A
	2-Butoxyethanol (CAS# 111-76-2):
	LC ₅₀ (Lepomis macrochirus)
	1490 mg/L, Exposure Time: 96 h, Test Type: Static
Toxicity to Aquatic Invertebrates:	Alcohol Ethoxylate (CAS# 68439-46-3):
	EC ₅₀ (Daphnia magna (water flea)):

PREPARED BY:
Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE: 2020-07-06

SECTION 12: ECOLOGICAL INFORMATION	
	5-10 mg/L, Exposure Time: 48 h, Test Type: N/A
	2-Butoxyethanol (CAS# 111-76-2):
	EC ₅₀ (Daphnia magna (water flea)):
	>1000 mg/L, Exposure Time: 48 h, Test Type: N/A
Persistence and degradability:	N/A

SECTION 13: DISPOSAL CONSIDERATIONS	
Recommended Waste Disposal Methods:	Reuse if possible. Otherwise dispose recovered material in accordance with all local, Provincial or Federal regulations.

Back to Top

SECTION 14: TRANSPORT INFORMATION	
Canadian TDG UN Number:	Not regulated.
UN Proper Shipping Name:	Not regulated.
Transport Hazard Class(es):	Not regulated.
Packing Group:	Not regulated.
Environmental Hazards:	Not available.
Special Precautions for User:	Not available.
Additional Information:	Not available.

Back to Top

SECTION 15: REGULATORY INFORMATION		
	HMIS	
HAZARD RATING INFORMATION	2 Health	
4 = Extreme	0 Flammability	
3 = High 2 = Moderate 1 = Slight 0 = Insignificant	0 Reactivity	
	B Personal protection	
	B = Safety glasses + Gloves	
HMIS Protection		
Group B		

PREPARED BY:
Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE: 2020-07-06

SECTION 15: REGULATORY INFORMATION



All pertinent hazard information has been provided in this SDS, per the requirements of the U.S. Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalent Standards, and the Canadian Workplace Hazardous Materials Identification System Standards (CPR 4).

Back to Top

SECTION 16: OTHER INFORMATION			
	ACRONYM LIST		
ACGIH	American Conference of Governmental Industrial Hygienists		
ATE	Acute Toxicity Estimate		
CAS	Chemical Abstracts Service		
CFR	Code of Federal Regulations		
DSL/NDSL	Domestic Substances List/ Non-domestic Substance List		
EC ₅₀	Half maximal effective concentration		
HMIS	Hazardous Materials Identification System		
IARC	International Agency for Research on Cancer		
LC ₅₀	Lethal concentration, 50%		
LD ₅₀	Lethal dose, 50%		
MSHA	Mine Safety and Health Administration		
N/A	Not Available		
NIOSH	The National Institute for Occupational Safety and Health		
N.O.S.	Not Otherwise Specified		
NTP	National Toxicology Program		
OSHA	Occupational Safety and Health Administration		
PEL	Permissible Exposure Limit		
PNOC	Particulates not otherwise classified		
PMMCC	Pensky-Martens Closed Cup		
Pow	Partition Coefficient Octanol: Water		
SDS	Safety Data Sheets		

PREPARED BY:
Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE: 2020-07-06

SECTION 16: OTHER INFORMATION		
STOT – SE	Specific Target Organ Toxicity – Single Exposure	
STOT – RE	Specific Target Organ Toxicity – Repeated Exposure	
TDG	Transportation of Dangerous Goods	
TLV	Threshold Limit Value	
UN	United Nations	
VOCs	Volatile Organic Compounds	
WEL	Workplace Exposure Limit	
WHMIS	Workplace Hazardous Materials Information System	

It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. Project Clean Inc. (formerly Maxim Chemical International Inc.) will accept no liability for damages or loss incurred from the improper handling and use of this product.

The information provided in the Safety Data Sheet has been obtained from current sources and is believed to be reliable.