

Safety Data Sheet Sections

| SECTION 1: IDENTIFICATION | 2 |
|--|---|
| SECTION 2: HAZARD IDENTIFICATION | 2 |
| PRECAUTIONARY STATEMENTS | 2 |
| SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS | 3 |
| SECTION 4: FIRST-AID MEASURES | |
| SECTION 5: FIRE-FIGHTING MEASURES | 4 |
| SECTION 6: ACCIDENTAL RELEASE MEASURES | 5 |
| SECTION 7: HANDLING AND STORAGE | 5 |
| SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION | 5 |
| EXPOSURE LIMITS: | 5 |
| INDIVIDUAL PROTECTION MEASURES / PERSONAL PROTECTIVE EQUIPMENT | 5 |
| SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES | 5 |
| SECTION 10: STABILITY AND REACTIVITY | e |
| SECTION 11: TOXICOLOGICAL INFORMATION | e |
| SECTION 12: ECOLOGICAL INFORMATION | 7 |
| SECTION 13: DISPOSAL CONSIDERATIONS | 7 |
| SECTION 14: TRANSPORT INFORMATION | 7 |
| SECTION 15: REGULATORY INFORMATION | 8 |
| SECTION 16: OTHER INFORMATION | 8 |
| ACRONYM LIST | 8 |

| SECTION 1: IDENTIFICATION | | |
|--|---|--|
| Product Trade Name: | Maxim Pine-O-Lux | |
| Product Code: | 1300862, 1300862lq | |
| Recommended Use: | Pine scent all-purpose cleaner | |
| Restrictions on Use: | For Industrial and Institutional use only | |
| Manufacturer Name: | Project Clean Inc. | |
| Manufacturer Address: | 1607 Derwent Way, Delta, B.C. Canada V3M 6K8 | |
| Manufacturer Phone Number: | 800-663-9925 | |
| Email Address of Competent Person Responsible for the SDS: | regulatory@projectclean.com | |
| Emergency Phone Number/ 24-Hour Number: | For Transportation Emergencies: Canutec <u>613-996-6666</u> Emergency Response Services: Chemtrec <u>800-424-9300</u> | |

Back to Top

| SECTION 2: HAZARD IDENTIFICATION | | |
|----------------------------------|---|--|
| Physical Hazards: | FLAMMABLE LIQUIDS – Category 3 | |
| Health Hazards: | SENSITIZATION – SKIN – Category 1 | |
| | SKIN CORROSION/ IRRITATION – Category 2 | |
| | EYE DAMAGE/ IRRITATION – Category 1 | |
| Symbol: | | |
| Signal word: | DANGER | |
| Hazard Statement: | H226 Flammable liquid and vapour. | |
| | H317 May cause an allergic skin reaction. | |
| | H315 Causes skin irritation. | |
| | H318 Causes serious eye damage. | |
| | PRECAUTIONARY STATEMENTS | |
| Prevention: | P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. | |
| | P233 Keep container tightly closed. | |
| | P240 Ground and bond container and receiving equipment. | |
| | P241 Use explosion-proof equipment. | |
| | P242 Use non-sparking tools. | |

PREPARED BY:
Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE: 2020-10-19

| | SECTION 2: HAZARD IDENTIFICATION |
|------------|--|
| | P243 Take action to prevent static discharges. |
| | P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. |
| | P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. |
| | P264 Wash hands and affected area thoroughly after handling. |
| | P272 Contaminated work clothing should not be allowed out of the workplace. |
| Responses: | P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| | P302 + P352 + P333 + P317 IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical help. |
| | P321 Specific treatment (see supplemental first aid information on this label). |
| | P362 + P364 Take off contaminated clothing and wash it before reuse. |
| | P305 + P351 + P338 + P317 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help. |
| | P370 + P378 In case of fire: Use water fog, alcohol foam or dry chemical to extinguish. |
| Storage: | P403 + P235 Store in a well-ventilated place. Keep cool. |
| Disposal: | P501 Dispose of contents/ container to an approved waste disposal plant. |

Back to Top

| SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS | | | |
|---|-------|----------------------|--|
| Ingredient Approx. Wt.% CAS Number | | | |
| Isopropyl Alcohol | 5-10 | 67-63-0 | |
| Terpineol/ Pine Oil | 1-5 | 8000-41-7/ 8002-09-3 | |
| Alcohol Ethoxylate | 1-5 | 68439-46-3 | |
| Fatty Acid, Tall Oil | 1-5 | 61790-12-3 | |
| D-Limonene | 0.1-1 | 112-34-5 | |

Back to Top

| SECTION 4: FIRST-AID MEASURES | | |
|-------------------------------|--|--|
| General Information: | Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. | |
| Inhalation: | Immediately remove the affected victim to fresh air. If symptoms persist, obtain medical attention. | |

PREPARED BY:
Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE: 2020-10-19

| SECTION 4: FIRST-AID MEASURES | | |
|---|---|--|
| Skin Contact: | Immediately flush exposed area with soap and water for at least 10 minutes. If irritation persists, or if contact has been prolonged, obtain medical attention. Remove contaminated clothing and launder before reuse. D-Limonene is a known skin sensitizer. | |
| Eye Contact: | Immediately flush with warm running water for at least 15 minutes, holding eyelids open during flushing. Remove contact lenses, if present and easy to do. If irritation persists, repeat flushing and obtain medical attention immediately. | |
| Ingestion: | Do not induce vomiting. If the victim is fully conscious, give plenty of clean water to drink to dilute product. Never give anything by mouth if victim is unconscious, is rapidly losing consciousness, or is convulsing. Call a Physician. | |
| Self-Protection of the First Aider: | Remove all sources of ignition. Ensure that first aid personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. | |
| Most Important Symptoms/ Effects, Acute and Delayed: | Ingestion: May burn mouth and throat. May cause gastrointestinal irritation or ulceration. Inhalation: May cause respiratory irritation. Eyes and skin: May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Brief contact may cause skin burns. | |
| If irritation occurs or persists, get medical attention. | | |

Back to Top

| SECTION 5: FIRE-FIGHTING MEASURES | | |
|---|--|--|
| Suitable Extinguishing Media: | Water fog, alcohol foam, or dry chemical. | |
| Unsuitable Extinguishing Media: | Do not use water jet as an extinguisher, as this will spread the fire. | |
| Flammability: | Flammable liquid and vapor. | |
| Flash Point: | 40°C (Pensky Martens Closed Cup) | |
| Special Firefighting Procedures: | Wear NIOSH/MSHA approved, self-contained breathing apparatus for firefighting situation. Use water spray to cool all nearby fire exposed surfaces. | |
| Unusual Fire / Explosion Hazards: | Avoid heat, flames and sparks. Avoid contact with Aldehydes, halogens, strong acids, strong oxidizing agents, alkalis, amines, ethylene oxide, halogenated hydrocarbons, isocyanates, do not use with aluminum equipment at temperatures above 50°C. | |
| Hazardous Decomposition Products: Carbon dioxide, carbon monoxide. The smoke may cunidentified toxic and/or irritating compounds. | | |

Back to Top

| SECTION 6: ACCIDENTAL RELEASE MEASURES | | |
|--|--|--|
| Environmental Protection Precautions: | Do not release to the environment or water source. | |
| Steps to be Taken in Case Material is Released or Spilled: | Wear protective equipment. Soak up spills with absorbents, then dispose of in an appropriate waste container. Keep material away from sewers. Reuse if possible. Otherwise dispose recovered material in accordance with all local, Provincial or Federal regulations. | |

Back to Top

| SECTION 7: HANDLING AND STORAGE | | |
|--|--|--|
| Precautions to be Taken in Handling and Storage: | Use good industrial hygiene. Do not get in eyes. Avoid contact with skin and clothing. Avoid breathing sprays or mists. Store in a cool, dry place away from incompatibles. Keep container closed when not in use. Do not mix with any other chemicals. Store at temperatures below 30°C and keep from freezing. | |

Back to Top

| SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION | | | |
|--|---|---------------------------|--|
| | EXPOSURE LIMITS: | | |
| OSHA (PEL): N/A | ACGIH TLV: N/A | Other exposure limit: N/A | |
| INDIVIDUAL PRO | TECTION MEASURES / PERSONAL PROT | ECTIVE EQUIPMENT | |
| Appropriate Engineering Controls: | Good general ventilation. | | |
| Skin Protection: | Hand Protection: Butyl rubber, neoprene, latex or nitrile gloves. Other Skin Protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Appropriate footwear should be selected based on the task being performed and the risks involved. | | |
| Eye and Face Protection: | Use chemical goggles or safety glasses. | | |
| Respiratory Protection: | In case of insufficient ventilation, wear suitable respiratory equipment. | | |
| Other Protective Equipment: | Eye wash, safety shower and full protective clothing recommended in the immediate work area. | | |

Back to Top

| SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES | | |
|---|--------------------------------|--|
| Appearance: | Clear yellowish/ green liquid. | |
| Odour: | Pine scent. | |
| Odour threshold: N/A | | |

| SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES | |
|--|-----------------------------------|
| pH: | 8.0-9.5 |
| Melting point/Freezing point: | N/A |
| Initial boiling point and boiling range: | N/A |
| Flash Point: | 40 °C (Pensky Martens Closed Cup) |
| Evaporation Rate (Water=1): | N/A |
| Flammability: | Flammable liquid and vapour. |
| Upper/Lower flammability or explosive limits: | None |
| Vapour pressure: | N/A |
| Vapour density: | N/A |
| Relative density/Specific gravity (Water = 1): | 0.99 @ 20°C |
| Solubility(ies): | Soluble in water |
| Partition coefficient: n-octanol/water: | N/A |
| Auto-ignition temperature: | N/A |
| Decomposition temperature: | N/A |
| Viscosity: | N/A |
| VOCs: | N/A |

Back to Top

| SECTION 10: STABILITY AND REACTIVITY | |
|--------------------------------------|--|
| Reactivity: | N/A |
| Chemical stability: | Stable under normal storage conditions. |
| Possibility of hazardous reactions: | This product is flammable. |
| Conditions to avoid: | Avoid heat, flames and sparks. Do not use with aluminum equipment at temperatures above 50°C. |
| Incompatibility: | Avoid contact with Aldehydes, halogens, strong acids, strong oxidizing agents, alkalis, amines, ethylene oxide, halogenated hydrocarbons, isocyanates. |
| Hazardous Decomposition Products: | Oxides of carbon. The smoke may contain unidentified toxic and/or irritating compounds. |

Back to Top

| SECTION 11: TOXICOLOGICAL INFORMATION | |
|---------------------------------------|-----------------------------------|
| Likely routes of exposure: | Skin and eye contact, inhalation. |

| SECTION 11: TOXICOLOGICAL INFORMATION | |
|---------------------------------------|---|
| Symptoms: | May cause mild irritation to eyes and skin. D-limonene is a known skin sensitizer. |
| Acute Toxicity Estimates: | LD ₅₀ (oral) > 2000 mg/kg |
| | LD ₅₀ (dermal) > 2000 mg/kg |
| | ATE _{mix} (inhalation, mist) 0.05-0.5 mg/L |
| Skin Sensitization: | <1% of the ingredients are classified as a skin sensitizer. |
| Germinal Cell Mutagenicity: | Data available on components indicates no potential germinal cell mutagenicity. |
| Reproductive Toxicity: | Data available on components indicates no potential reproductive toxicity. |
| Carcinogenicity: | D-limonene (CAS# 5989-27-5) is listed as Group 3 carcinogen by IARC. Group 3 – Not Classifiable as to Carcinogenicity in Humans |
| Aspiration Hazard: | Data available on components indicates no potential aspiration hazard. |

Back to Top

| SECTION 12: ECOLOGICAL INFORMATION | |
|------------------------------------|--|
| Toxicity to Fresh Water Algae: | D-Limonene (CAS# 5989-27-5): |
| | EC ₅₀ (Desmodesmus subspicatus (green algae)) |
| | 150 mg/L, Exposure Time: 72 h, Test Type: Static |
| Toxicity to Fish Species: | D-Limonene (CAS# 5989-27-5): |
| , , | LC ₅₀ (Pimephales promeals) |
| | 0.702 mg/L, Exposure Time, 96 h, Test Type: Flow-Through |
| Toxicity to Aquatic Invertebrates: | D-Limonene (CAS# 5989-27-5): |
| , . | EC ₅₀ (Daphnia magna (water flea)): |
| | 0.36 mg/L, Exposure Time: 48 h, Test Type: Static |
| Persistence and degradability: | N/A |

Back to Top

| SECTION 13: DISPOSAL CONSIDERATIONS | |
|---|--|
| Recommended Waste Disposal Reuse if possible. Otherwise dispose recovered material in accordance with all local, Provincial or Federal regulations. | |

Back to Top

| SECTION 14: TRANSPORT INFORMATION | |
|-----------------------------------|--|
| Canadian TDG UN Number: | 1993 |
| UN Proper Shipping Name: | FLAMMABLE LIQUID, N.O.S. (isopropyl alcohol) |
| Transport Hazard Class(es): | 3 |

PREPARED BY:LAST UPDATE:Regulatory DivisionPage 7 of 92020-10-19

Project Clean Inc.

| SECTION 14: TRANSPORT INFORMATION | |
|-----------------------------------|----------------------------------|
| Packing Group: | III |
| Environmental Hazards: | Not available. |
| Special Precautions for User: | Not available. |
| Additional Information: | Limited Quantity Index: 5 Litres |

Back to Top

| SECTION 15: REGULATORY INFORMATION | | |
|------------------------------------|-----------------------------|--|
| | HMIS | |
| HAZARD RATING INFORMATION | 3 Health | |
| 4 = Extreme | 2 Flammability | |
| 3 = High 2 = Moderate | 0 Reactivity | |
| 1 = Slight 0 = Insignificant | B Personal protection | |
| | B = Safety Glasses + Gloves | |
| HMIS Protection Group B | D = Salety Glasses + Gloves | |

All pertinent hazard information has been provided in this SDS, per the requirements of the U.S. Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalent Standards, and the Canadian Workplace Hazardous Materials Identification System Standards (CPR 4).

Back to Top

| SECTION 16: OTHER INFORMATION | |
|-------------------------------|---|
| ACRONYM LIST | |
| ACGIH | American Conference of Governmental Industrial Hygienists |
| ATE | Acute Toxicity Estimate |
| CAS | Chemical Abstracts Service |
| CFR | Code of Federal Regulations |
| DSL/NDSL | Domestic Substances List/ Non-domestic Substance List |

PREPARED BY:
Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE: 2020-10-19

| | SECTION 16: OTHER INFORMATION |
|------------------|---|
| EC ₅₀ | Half maximal effective concentration |
| HMIS | Hazardous Materials Identification System |
| IARC | International Agency for Research on Cancer |
| LC ₅₀ | Lethal concentration, 50% |
| LD ₅₀ | Lethal dose, 50% |
| MSHA | Mine Safety and Health Administration |
| N/A | Not Available |
| NIOSH | The National Institute for Occupational Safety and Health |
| N.O.S. | Not Otherwise Specified |
| NTP | National Toxicology Program |
| OSHA | Occupational Safety and Health Administration |
| PEL | Permissible Exposure Limit |
| PNOC | Particulates not otherwise classified |
| PMMCC | Pensky-Martens Closed Cup |
| Pow | Partition Coefficient Octanol: Water |
| SDS | Safety Data Sheets |
| STOT – SE | Specific Target Organ Toxicity – Single Exposure |
| STOT – RE | Specific Target Organ Toxicity – Repeated Exposure |
| TDG | Transportation of Dangerous Goods |
| TLV | Threshold Limit Value |
| UN | United Nations |
| VOCs | Volatile Organic Compounds |
| WEL | Workplace Exposure Limit |
| WHMIS | Workplace Hazardous Materials Information System |

Back to Top

It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. Project Clean Inc. (formerly Maxim Chemical International Inc.) will accept no liability for damages or loss incurred from the improper handling and use of this product.

The information provided in the Safety Data Sheet has been obtained from current sources and is believed to be reliable.