

SECTION 1: Identification

1.1. Product identifier

Product name : FLOOR STRIPPER
Product code : A100210

1.2. Recommended use and restrictions on use

Recommended use : ECOLOGO® certified non-corrosive floor stripper
Restrictions on use : Industrial and commercial use only

1.3. Supplier

Project Clean Inc.
12 James St N, Suite 201 A
Hamilton, ON L8R 2J9
Canada

regulatory@projectclean.com - www.projectclean.ca

1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call CANUTEC CANADA OR CHEMTREC USA 24hr/day 7days/week
Within USA and Canada: CANADA: 613 996 6666 or *666 on a cell phone | USA: 800 424 9300

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin corrosion/irritation, Category 1	H314	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS CA) : H314 - Causes severe skin burns and eye damage.

Precautionary statements (GHS CA) : P260 - Do not breathe mist/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

protection.

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P363 - Wash contaminated clothing before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local/provincial/federal regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Monoethanolamine	Monoethanolamine	CAS-No.: 141-43-5	5 – 10
2-Phenoxyethanol	2-Phenoxyethanol	CAS-No.: 122-99-6	5 – 10
Caprylic acid	Octanoic acid ; Caprylic acid	CAS-No.: 124-07-2	1 – 5
Alcohol Ethoxylate	Ethoxylated alcohols (C=7-21)	CAS-No.: 68991-48-0	1 – 5

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
First-aid measures general	: Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe mist/spray. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in dry, cool, well-ventilated area. Store in original container. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Monoethanolamine (141-43-5)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Ethanolamine (2-Aminoethanol)
OEL TWA	7.5 mg/m ³
OEL TWA [ppm]	3 ppm
OEL STEL	15 mg/m ³
OEL STEL [ppm]	6 ppm
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	2-Aminoethanol (Ethanolamine)
VECD (OEL STEL)	15 mg/m ³
VECD (OEL STEL) [ppm]	6 ppm
VEMP (OEL TWA)	7.5 mg/m ³
VEMP (OEL TWA) [ppm]	3 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Ethanolamine

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Monoethanolamine (141-43-5)	
OEL TWA [ppm]	3 ppm
OEL STEL [ppm]	6 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Ethanolamine
OEL TWA [ppm]	3 ppm
OEL STEL [ppm]	6 ppm
Notations and remarks	TLV® Basis: Eye & skin irr
Regulatory reference	ACGIH 2022
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Ethanolamine
OEL TWA [ppm]	3 ppm
OEL STEL [ppm]	6 ppm
Notations and remarks	Eye & skin irr
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Ethanolamine
OEL TWA [ppm]	3 ppm
OEL STEL [ppm]	6 ppm
Notations and remarks	TLV® Basis: Eye & skin irr
Regulatory reference	ACGIH 2022
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Ethanolamine
OEL TWA [ppm]	3 ppm
OEL STEL [ppm]	6 ppm
Notations and remarks	TLV® Basis: Eye & skin irr
Regulatory reference	ACGIH 2022
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Ethanolamine

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Monoethanolamine (141-43-5)	
OEL TWA [ppm]	3 ppm
OEL STEL [ppm]	6 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Ethanolamine
OEL TWA [ppm]	3 ppm
OEL STEL [ppm]	6 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Ethanolamine
OEL TWA [ppm]	3 ppm
OEL STEL [ppm]	6 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Ethanolamine
OEL TWA [ppm]	3 ppm
OEL STEL [ppm]	6 ppm
Notations and remarks	TLV® Basis: Eye & skin irr
Regulatory reference	ACGIH 2022
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Ethanolamine
OEL TWA [ppm]	3 ppm
OEL STEL [ppm]	6 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanolamine
ACGIH OEL TWA [ppm]	3 ppm
ACGIH OEL STEL [ppm]	6 ppm

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Monoethanolamine (141-43-5)	
Remark (ACGIH)	TLV® Basis: Eye & skin irr
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Ethanolamine
OSHA PEL TWA [1]	6 mg/m ³
OSHA PEL TWA [2]	3 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
2-Phenoxyethanol (122-99-6)	
Canada (Ontario) - Occupational Exposure Limits	
Local name	2-Phenoxyethanol
OEL TWA	141 mg/m ³
OEL TWA [ppm]	25 ppm
Notations and remarks	Skin
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear. Yellow liquid.
Colour	: Yellow
Odour	: Characteristic odour
Odour threshold	: No data available
pH	: 10 – 12
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 100 °C
Auto-ignition temperature	: Not self-igniting
Decomposition temperature	: No data available
Flammability	: Not flammable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1 – 1.02
Solubility	: soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: Thin like water
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Temperatures above 30oC (86oF) and below 5oC (41oF).

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Incompatible materials	: Organic materials. Oxidizing agent. Strong acids. Metals.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Monoethanolamine (141-43-5)	
LD50 oral rat	1089 mg/kg Source: OECD SIDS
LD50 dermal rabbit	2504 mg/kg Source: OECD SIDS
LC50 Inhalation - Rat (Vapours)	> 1487 mg/l Source: ECHA
ATE CA (oral)	1089 mg/kg bodyweight
ATE CA (Dermal)	2504 mg/kg bodyweight
2-Phenoxyethanol (122-99-6)	
LD50 oral rat	1850 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	14391 mg/kg (24 h, Rat, Male / female, Dermal, 48 day(s))
LD50 dermal rabbit	> 2214 mg/kg bodyweight Animal: rabbit, Guideline: other:
LC50 Inhalation - Rat	> 1 mg/l (OECD 412: Repeated Dose Inhalation Toxicity:28/14-Day, 6 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
ATE CA (oral)	500 mg/kg bodyweight
Caprylic acid (124-07-2)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
Alcohol Ethoxylate (68991-48-0)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation : Causes severe skin burns.

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

2-Phenoxyethanol (122-99-6)	
LOAEL (oral, rat, 90 days)	> 700 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
LOAEL (dermal, rat/rabbit, 90 days)	> 500 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEL (dermal, rat/rabbit, 90 days)	500 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Monoethanolamine (141-43-5)	
LC50 - Fish [1]	170 mg/l Source: OECD SIDS
EC50 - Crustacea [1]	32.6 mg/l
ErC50 algae	2.1 mg/l Source: ECHA
Partition coefficient n-octanol/water (Log Pow)	-1.31 Source: ICSC

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-Phenoxyethanol (122-99-6)	
LC50 - Fish [1]	220 – 460 mg/l (DIN 38412: German standard methods for the examination of water, waste water and sludge, 96 h, <i>Leuciscus idus</i> , Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	> 500 mg/l (Equivalent or similar to OECD 202, 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, Behaviour)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, <i>Desmodesmus subspicatus</i> , Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	500 mg/l Source: IUCLID
Partition coefficient n-octanol/water (Log Pow)	1.2 (Experimental value, EU Method A.8: Partition Coefficient, 23 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.6 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Caprylic acid (124-07-2)	
LC50 - Fish [1]	22 mg/l (US EPA, 96 h, <i>Lepomis macrochirus</i> , Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 20 mg/l (OECD 202: <i>Daphnia</i> sp. Acute Immobilisation Test, 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [1]	43.73 mg/l (OECD 201: Alga, Growth Inhibition Test, <i>Pseudokirchneriella subcapitata</i> , Static system, Fresh water, Experimental value, Growth rate)
EC50 72h - Algae [2]	23.28 mg/l Test organisms (species): <i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i>)
BCF - Fish [1]	234 – 288 (Equivalent or similar to OECD 305, 28 day(s), <i>Danio rerio</i> , Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.05 (Experimental value)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.46 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Alcohol Ethoxylate (68991-48-0)	
LC50 - Fish [1]	70.1 mg/l 48 hours
EC50 - Crustacea [1]	5.3 mg/l <i>Daphnia</i> , 48 hours
EC50 96h - Algae [1]	3.389 mg/l Source: EPI SUITE

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

12.2. Persistence and degradability

Persistence and degradability This product does not exhibit the properties of ignitability, corrosivity, reactivity or environmentally persistent toxicity. This product does not adversely inhibit a diverse aquatic range of organisms (animal, plant, bacteria) as required by the Ecologo® program under UL2759.

2-Phenoxyethanol (122-99-6)	
Persistence and degradability	Readily biodegradable in water.
Caprylic acid (124-07-2)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.27 g O ₂ /g substance
Alcohol Ethoxylate (68991-48-0)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

Monoethanolamine (141-43-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.31 Source: ICSC
2-Phenoxyethanol (122-99-6)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	1.2 (Experimental value, EU Method A.8: Partition Coefficient, 23 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.6 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Caprylic acid (124-07-2)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	234 – 288 (Equivalent or similar to OECD 305, 28 day(s), Danio rerio, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.05 (Experimental value)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.46 (log Koc, SRC PCKOCWIN v2.0, QSAR)

12.4. Mobility in soil

Mobility in soil No (test) data on mobility of the substance available

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Monoethanolamine (141-43-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.31 Source: ICSC
2-Phenoxyethanol (122-99-6)	
Surface tension	70.7 mN/m (20 °C, 1 g/l, EU Method A.5: Surface tension)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.6 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Partition coefficient n-octanol/water (Log Pow)	1.2 (Experimental value, EU Method A.8: Partition Coefficient, 23 °C)
Caprylic acid (124-07-2)	
Surface tension	33.7 mN/m (23 °C, 0.6 g/l, EU Method A.5: Surface tension)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.46 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.05 (Experimental value)
Alcohol Ethoxylate (68991-48-0)	
Mobility in soil	589.5 Source: EPI SUITE

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Reuse if possible. Otherwise dispose recovered material in accordance with all local, Provincial or Federal regulations.

Product/Packaging disposal recommendations : Non-refillable container. Do not reuse or refill this container. Offer for recycling, if available or puncture and dispose of in a sanitary landfill.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No. (TDG) : UN2491

14.2. UN proper shipping name

Proper Shipping Name (TDG) : ETHANOLAMINE SOLUTION

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Transport document description (TDG) : UN2491 ETHANOLAMINE SOLUTION, 8, III

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : 8

Hazard labels (TDG) : 8



14.4. Packing group

Packing group (TDG) : III

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Avoid release to the environment.

TDG

UN-No. (TDG) : UN2491

Explosive Limit and Limited Quantity : 5 L

Index

Excepted quantities (TDG) : E1

Passenger Carrying Road Vehicle or : 5 L

Passenger Carrying Railway Vehicle

Index

Emergency Response Guide (ERG) : 153

Number

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

Monoethanolamine (141-43-5)

Listed on the Canadian DSL (Domestic Substances List)

2-Phenoxyethanol (122-99-6)

Listed on the Canadian DSL (Domestic Substances List)

FLOOR STRIPPER

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Caprylic acid (124-07-2)

Listed on the Canadian DSL (Domestic Substances List)

Alcohol Ethoxylate (68991-48-0)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: Other information

Issue date : 07/25/2022

Full text of H-statements:

H314	Causes severe skin burns and eye damage.
------	--

H318	Causes serious eye damage.
------	----------------------------

It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. Project Clean Inc. will accept no liability for damages or loss incurred from the improper handling and use of this product.

The information provided in the Safety Data Sheet has been obtained from current sources and is believed to be reliable.