

## FLOOR CARE

## Benefits

Low maintenance finish • Economical

BENEFITS is a unique fast-drying, high gloss, low maintenance floor finish that provides exceptional appearance, clarity and wear characteristics. It levels easily and dries quickly to a durable clear gloss film that provides outstanding resistance to marks, scuffing, maintenance cleaning and heavy traffic. BENEFITS is a blend of extremely hard, new generation acrylic terpolymers, thermoplastics, resins, and plasticizers. This versatile floor finish can be used with or without burnishing depending upon foot traffic. BENEFITS requires less burnishing, recoating and stripping. Excellent choice for schools, supermarkets, factories, and manufacturing facilities.

- Low mop drag and outstanding leveling
- 16% non-volatile solids, high gloss, tough & durable coating
- Resists black heel marks and scuffing
- Use with or without a sealer

## APPLICATIONS

Vinyl composite  
PVC  
Linoleum  
Sheet vinyl  
Marmoleum

Quarry tile  
Terrazzo  
Concrete  
Marble



## TECHNICAL DATA

**Appearance:** liquid  
**Colour:** pearl white  
**Foam:** none  
**Odour:** mild, no added fragrance  
**pH:** 8.0-8.5

## Packaging size

4 x 3.78L  
18.9L pail

## Packaging codes

P303131-4cs  
P303131-18.9



PROMAX®

# DIRECTIONS

## General Application:

1. Completely strip all old wax or floor finish with a floor finish remover like FINISH REMOVER or #1 REMOVER.
2. Remove the stripping solution and follow with one or two clear-water rinses. Allow floor to dry.
3. For extra durability, two coats of FLOOR SEALER can be applied but is not required.
4. Apply BENEFITS in a uniform, thin coat. Let dry thoroughly for 20 to 30 minutes depending upon the surrounding air flow, temperature and humidity. Do not apply additional coats until surface is dry to the touch. Apply additional coats following the same techniques. Applying three to five coats is optimum.

## General Maintenance:

1. Dust mop or sweep floor as necessary with a clean dust mop.
2. Damp mop using a neutral pH floor cleaner such as NEUTRAL CLEAN or NEUTRAPOWER.
3. High traffic areas can be quickly repaired between finish applications by using a mop on restorer or spray buffing solution such as ARMOR-ACE, MAXICOAT or FLOOR FINISH 18. These high traffic lanes can be recoated as needed.
4. Heavily soiled areas can be machine scrubbed using HD FLOOR CLEAN at the recommended dilutions and the appropriate floor scrubbing pad.

## Application:

Ready-to-use

---

# STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

# SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at [projectclean.com](http://projectclean.com) or by calling 1-800-663-9925. Improper use may result in damage or injury.

