

FLOOR CARE

Maxicoat

2 in 1 hard floor cleaner and gloss restorer • Concentrated formula



MAXICOAT is a concentrated blend of high-performance cleaning agents and high gloss ingredients. Produces a clean and bright floor surface when used with an automatic scrubber or mop bucket system. A thin coat of thermoplastic polymers is left on the floor surface during cleaning process. For best results burnish floor after auto scrubbing to achieve maximum gloss. MAXICOAT can also be applied with a mop and bucket system. MAXICOAT is versatile enough to be used with ultra-high speed burnishers or conventional speed buffers.

- Will not yellow or discolor
- Penetrates existing floor finish to provide better bonding and adhesion
- Use with low, high or ultra-high speed buffing and burnishing equipment
- Unsurpassed response to burnishing
- Reduces the need for frequent stripping
- Improves any floor finishes blackmark and scuff resistance

APPLICATIONS

Resilient Flooring
Quarry tile
Terrazzo
Concrete



TECHNICAL DATA

Appearance: liquid
Colour: milky white
Foam: none
Odour: Slight ammonia odour
pH: 7.5-8.0

Packaging size

4 x 3.78L
18.9L pail

Packaging codes

1300695-4cs
1300695-18.9



PROMAX®

DIRECTIONS

Covers up to 10,000 to 12,500 square feet per gallon.

General Application:

Hard floor auto scrubbing:

1. Add 32 ml of MAXICOAT per each litre of cold water in solution tank. (4 oz/gal) (1:32)
2. Once floor has been properly swept, scrub the floor using a conventional "one pass" method. Use white or red pads with light pad pressure to avoid rubbing away finish.
3. Mop up solution behind machine immediately.
4. Let the floor thoroughly dry. Burnishing is optional. To obtain maximum overall gloss burnishing is recommended.
5. To remove deeply embedded dirt use HD FLOOR CLEAN according to label directions.

Hard floor mop on:

1. Add 16 ml of MAXICOAT per each litre of cold water in the mop bucket. (2 oz/gal) (1:64)
2. Apply MAXICOAT solution liberally to the floor area being cleaned.
3. Mop up soil and excess cleaner with a tightly wrung out cleaning mop.
4. Let the floor thoroughly dry. To obtain maximum gloss burnish with a high-speed machine.

To remove deeply embedded dirt use HD FLOOR CLEAN according to label directions.

Application:

Hard floor auto scrubbing	1:32
Hard floor mop on	1:64

STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

