#### **FLOOR CARE**

# **#1 Remover**

Fast acting formula · High performance floor stripper

#1 REMOVER is a high-performance floor finish remover that effectively breaks down existing finishes, non-permanent sealers and heavy buildup. Designed for fast-action, #1 REMOVER can be used on a variety of flooring such as resilient tile, terrazzo, marble, stone, vinyl, vinyl composites, sealed wood and laminates.

- For all types of flooring
- Low VOCs

Fast acting

### **APPLICATIONS**

Vinyl composite

**PVC** 

Sheet vinyl

Quarry tile

Terrazzo Concrete

Marble







# **TECHNICAL DATA**

Appearance: clear liquid

Colour: colourless

Foam: none

Odour: ammoniacal

**pH:** >12.0



P303531-4cs P303531-18.9

Packaging size

4 x 3.78L 18.9L pail





#### **DIRECTIONS**

#### **General Application:**

- 1. Dust mop entire surface to be stripped.
- 2. Dilute #1 REMOVER with cold or warm water according to the level of finish build-up. (See dilution ratios below). Apply this dilution to an area approximately 10 ft x 10 ft and allow 5 minutes for #1 REMOVER to liquefy the finish. Do not permit the floor remover to dry on the floor.
- 3. Scrub thoroughly with a floor machine using a black or hi-pro pad or agitate with a doodle bug holder and a pad longer dwell times may be required.
- 4. Pick up the solution with a wet-vac, auto-scrubber or mop and rinse the floor with NEUTRAPOWER or NEUTRAL CLEAN at a dilution of 8 ml per litre of cold water (1 oz/gallon) (1:128).

For Heavy Finish Build-up: Use 200 ml per litre of water (26 oz/gallon) (1:5).

For Light Finish Build-up: Use 100 ml per litre of water (13 oz/gallon) (1:10).

NOTE: Test flooring compatibility with #1 REMOVER before use.

#### **Application:**

Heavy finish build-up 1:5 Light finish build-up 1:10

## **STORAGE**

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

# SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

