

FLOOR CARE

#1 Remover

Fast acting formula · High performance floor stripper

#1 REMOVER is a high-performance floor finish remover that effectively breaks down existing finishes, non-permanent sealers and heavy buildup. Designed for fast-action, #1 REMOVER can be used on a variety of flooring such as resilient tile, terrazzo, marble, stone, vinyl, vinyl composites, sealed wood and laminates.

- For all types of flooring
- Fast acting
- Low VOCs

APPLICATIONS

Vinyl composite
PVC
Sheet vinyl
Quarry tile

Terrazzo
Concrete
Marble



TECHNICAL DATA

Appearance: clear liquid

Color: colorless

Foam: none

Odor: ammoniacal

pH: >12.0

Packaging size

4 x 1 US Gallon
5 Gallon Pail

Packaging codes

P303531U-4c22
P303531U-5gal



PROMAX®

DIRECTIONS

General Application:

1. Dust mop entire surface to be stripped.
2. Dilute #1 REMOVER with cold or warm water according to the level of finish build-up. (See dilution ratios below). Apply this dilution to an area approximately 10 ft x 10 ft and allow 5 minutes for #1 REMOVER to liquefy the finish. Do not permit the floor remover to dry on the floor.
3. Scrub thoroughly with a floor machine using a black or hi-pro pad or agitate with a doodle bug holder and a pad – longer dwell times may be required.
4. Pick up the solution with a wet-vac, auto-scrubber or mop and rinse the floor with NEUTRAPOWER or NEUTRAL CLEAN at a dilution of 1 oz per US gallon of cold water (8 ml/litre) (1:128).

Heavy finish build-up: Use 26 oz per US gallon of water (200 ml/litre) (1:5).

Light finish build-up: Use 13 oz per US gallon of water (100 ml/litre) (1:10).

NOTE: Test flooring compatibility with #1 REMOVER before use.

Application:

Heavy finish build-up	1:5
Light finish build-up	1:10

STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

