

FLOOR CARE

Foundation

Multi-surface floor finish · High gloss

FOUNDATION provides maximum gloss and durability to extend the life and improve the appearance of floors. Its superior scratch, scuff and blackmark resistance is a result of a high-performance blend of tough, hard and flexible polymers. Its plasticized ingredients give excellent burnish response and can be used with or without a sealer. FOUNDATION's fast drying formulation builds gloss quickly and responds with unmatched brilliance to burnishing by 1000 to 3000 rpm machines. However, burnishing is not required to maintain its high gloss and outstanding appearance. FOUNDATION achieves levels of hardness and clarity far superior to conventional finishes. It can be used on almost any type of flooring except unsealed wood, cork, or conductive flooring.

- Resists blackmarks and scuffing
- Dries quickly without fisheyes, craters or streaks
- Durable 18% non-volatile solids
- Use with or without a sealer

APPLICATIONS

Vinyl composite
PVC
Linoleum
Sheet vinyl
Marmoleum

Quarry tile
Terrazzo
Concrete
Marble



TECHNICAL DATA

Appearance: liquid
Color: pearl white
Foam: none
Odor: slight ammonia odor
pH: 8.0-9.0

Packaging size
4 x 1 US Gallon
5 Gallon Pail

Packaging codes
P303543U-4c22
P303543U-5gal



DIRECTIONS

General Application:

1. Completely strip all old wax or finish with a finish remover such as #1 REMOVER or FINISH REMOVER.
2. Remove the stripping solution and follow with one or two clear-water rinses. Allow floor to dry.
3. For extra durability, two coats of FLOOR SEALER or HOLDOUT can be applied but is not required.
4. Apply FOUNDATION in a uniform, thin coat. Let dry thoroughly for 20 to 30 minutes depending upon the surrounding air flow, temperature, and humidity. Do not apply additional coats until surface is dry to the touch. Apply additional coats following the same techniques. Applying three to five coats is optimum.

General Maintenance:

1. Dust mop or sweep floor as necessary with a clean dust mop.
2. Damp mop using a neutral pH floor cleaner such as NEUTRAL CLEAN or NEUTRAPOWER
3. High traffic areas can be quickly repaired between finish applications by using a mop on restorer like ARMOR-ACE, MAXICOAT or FLOOR FINISH 18. High traffic lanes can be recoated as needed.
4. Heavily soiled areas can be machine scrubbed using HD FLOOR CLEANER at the recommended dilutions and appropriate floor scrubbing pad.

Application:

Ready-to-use

STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

PROMAX®