

## FLOOR CARE

# Holdout

Semi-permanent sealer • Waterproof protectant



HOLDOUT is a topcoat or undercoat sealer for porous or worn floors and when water resistance is needed. HOLDOUT is a specially modified water emulsion synthetic polymer sealer for a wide range of resilient floor surfaces including vinyl composition tile, concrete, quarry, terrazzo and other stone or composite hard floor surfaces. HOLDOUT has outstanding chemical and water resistance and is carefully designed to work with any flooring finish applied after sealing. Using HOLDOUT helps protect the flooring material from excess wear and spills, prolonging the life of the flooring.

- Clear seal with no discoloration
- Excellent water and chemical resistance
- Superior adhesion characteristic
- Prolongs time between strip and recoat
- Low odour

## APPLICATIONS

Resilient flooring

Quarry tile

Terrazzo

Concrete



## TECHNICAL DATA

**Appearance:** liquid**Colour:** opaque white**Foam:** none**Odour:** mild, no added fragrance**pH:** 8.5-9.0**Packaging size**

4 x 3.78L  
18.9L pail

**Packaging codes**

1300600-4cs  
1303600-18.9



# PROMAX®

## DIRECTIONS

Covers 93 to 189 square meters per litre depending on porosity of flooring. It may be removed with a solution of #1 REMOVER at a dilution of 1000 mL per litre of water (128 oz/gallon) (1:1).

### General Application:

1. Completely strip old floor finish with a floor finish remover such as FINISH REMOVER or #1 REMOVER.
2. Remove the stripping solution and rinse floor with a neutral pH cleaner such as NEUTRAPOWER and NEUTRAL CLEAN or follow with two to three clear water rinses. Allow to dry.
3. Use a clean finish mop, either fine string or candy striped. Pre-wet with water and wring out mop to conserve finish.
4. Apply an even coat of HOLDOUT in a uniform and medium coat. Let dry thoroughly – approximately 30-40 minutes between coats. One sealer coat is usually all that is needed before applying a floor finish on top. On older, worn or porous surfaces a second coat may be applied. HOLDOUT can be top coated with any one of Project Clean's quality floor finishes.

### Application on new concrete (no less than 90 days old):

1. Acid washed the surface and rinse thoroughly.
2. Apply HOLDOUT as directed above.

### Application:

Concrete	1:1
General application	Ready-to-use

---

## STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

## SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at [projectclean.com](http://projectclean.com) or by calling 1-800-663-9925. Improper use may result in damage or injury.

