

FLOOR CARE

# Maxicoat

2 in 1 hard floor cleaner and gloss restorer · Concentrated formula

MAXICOAT is a concentrated blend of high-performance cleaning agents and high gloss ingredients. Produces a clean and bright floor surface when used with an automatic scrubber or mop bucket system. A thin coat of thermoplastic polymers is left on the floor surface during cleaning process. For best results burnish floor after auto scrubbing to achieve maximum gloss. MAXICOAT can also be applied with a mop and bucket system.

- Will not yellow or discolor
- Restores moisturizers to the floor finish to keep it from powdering
- Unsurpassed response to burnishing
- Reduces the need for frequent stripping

## APPLICATIONS

Vinyl composite  
PVC  
Linoleum  
Sheet vinyl  
Marmoleum

Quarry tile  
Terrazzo  
Concrete  
Marble



## TECHNICAL DATA

**Appearance:** liquid  
**Color:** milky white  
**Foam:** none  
**Odor:** Slight ammonia odor  
**pH:** 7.5-8.0

**Packaging size**  
4 x 1 US Gallon  
5 Gallon Pail

**Packaging codes**  
P303695U-4c22  
P303695U-5gal



# DIRECTIONS

## General Application:

### Hard floor auto scrubbing:

1. Add 4 oz. of MAXICOAT per each gallon of cold water in solution tank (32ml/litre) (1:32).
2. Once floor has been properly swept, scrub the floor using a conventional "one pass" method. Use white or red pads with light pad pressure to avoid rubbing away finish.
3. Mop up solution behind machine immediately.
4. Let the floor thoroughly dry. Burnishing is optional. To obtain maximum overall gloss burnishing is recommended.
5. To remove deeply embedded dirt use HD FLOOR CLEAN according to label directions.

### Hard floor mop on:

1. Add 2 oz. of MAXICOAT per each gallon of cold water in the mop bucket (16ml/litre)(1:64).
2. Apply MAXICOAT solution liberally to the floor area being cleaned.
3. Mop up soil and excess cleaner with a tightly wrung out cleaning mop.
4. Let the floor thoroughly dry. To obtain maximum gloss burnish with a high-speed machine.

To remove deeply embedded dirt use HD FLOOR CLEAN according to label directions.

## Application:

Hard floor auto scrubbing	1:32
Hard floor mop on	1:64

---

## STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

## SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at [projectclean.com](http://projectclean.com) or by calling 1-800-663-9925. Improper use may result in damage or injury.

**PROMAX**®