

FLOOR CARE

Mirage

High solids floor finish · Burnishable gloss

MIRAGE leaves your floors with a deep, wet-look gloss long after they are dry; and offers all the durability of a dri-brite floor finish plus a superior ultra high-speed burnishing response. The high content of over 20% solids means fewer coats to achieve maximum results. With reduced costs combined with excellent detergent resistance to repeat cleaning cycles, MIRAGE yields a lower cost than most competitive products on the market. It can be used on most types of resilient flooring such as linoleum, marmoleum, vinyl sheet and vinyl composite tile.

- Long wear in high traffic locations
- Rapid leveling
- Dries streak-free
- High solids content

APPLICATIONS

Vinyl composite
PVC
Linoleum
Sheet vinyl
Marmoleum

Quarry tile
Terrazzo
Concrete
Marble



TECHNICAL DATA

Appearance: opaque liquid
Color: milky white
Foam: none
Odor: slight ammonia odor
pH: 8.5-9.0

Packaging size

4 x 1 US Gallon
5 Gallon Pail

Packaging codes

P303705U-4c22
P303705U-5gal

PROMAX®

DIRECTIONS

General Application:

1. Completely strip all old wax or finish with a finish remover such as #1 REMOVER or FINISH REMOVER.
2. Remove the stripping solution and follow with one or two clear-water rinses. Allow floor to dry.
3. For extra durability, two coats of FLOOR SEALER or HOLDOUT can be applied but is not required.
4. Apply MIRAGE in a uniform, thin coat. Let dry thoroughly for 20 to 30 minutes depending upon the surrounding air flow, temperature and humidity. Do not apply additional coats until surface is dry to the touch. Apply additional coats following the same techniques. Applying three to five coats is optimum.

General Maintenance:

1. Dust mop or sweep floor as necessary with a clean dust mop.
2. Damp mop using a neutral pH floor cleaner such as NEUTRAL CLEAN or NEUTRAPOWER
3. High traffic areas can be quickly repaired between finish applications by using a mop on restorer like ARMOR-ACE, MAXICOAT or FLOOR FINISH 18. High traffic lanes can be recoated as needed.
4. Heavily soiled areas can be machine scrubbed using HD FLOOR CLEAN at the recommended dilutions and the appropriate floor scrubbing pad.

Burnishing: Burnish as desired to maintain gloss using burnish pad.

TIP: A sealer is not required, but if you have a very porous floor, it may be advantageous to apply HOLDOUT or FLOOR SEALER. Two coats are often sufficient.

Application:

Ready-to-use

STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

PROMAX®