

FLOOR CARE

Max Shine

Durable floor finish · Burnishable gloss

MAX SHINE is a water-based acrylic polyurethane floor finish with 20% solids. It delivers an outstanding high gloss to bring out a floor's natural beauty. Its unique chemistry enables it to be applied in thin coats for maximum coverage with excellent durability, re-coatability and removability. MAX SHINE can be applied on a variety of floors such as linoleum, marmoleum, vinyl, tile, marble, concrete, and sealed wood. It can be used alone or paired with a high-quality sealer such as HOLDOUT and FLOOR SEALER to enhance the protection of the floor.

- 20% solid
- Burnishable high gloss
- Blackmark resistance
- Rapid drying time

APPLICATIONS

Vinyl composite
PVC
Linoleum
Sheet vinyl
Marmoleum

Quarry tile
Terrazzo
Concrete
Marble



TECHNICAL DATA

Appearance: liquid
Color: pearl white
Foam: none
Odor: slight ammonia odor
pH: 8.5-9.0

Packaging size
4 x 1 US Gallon
5 Gallon Pail

Packaging codes
P303698U-4c22
P303698U-5gal



DIRECTIONS

General Application:

1. Completely strip old floor finish with a floor finish remover such as FINISH REMOVER or #1 REMOVER
2. Remove the stripping solution and rinse floor with a neutral pH cleaner such as NEUTRAPOWER and NEUTRAL CLEAN or follow with two to three clear water rinses. Allow to dry.
3. Apply MAX SHINE in a uniform, thin coat with either fine string mop or finish applicator. Allow finish to dry thoroughly for 20- 30 minutes depending upon the surrounding air flow, temperature, and humidity. Do not apply additional coats until surface is dry to the touch.
4. Apply additional coats following the same techniques. Applying three to five coats is optimum.

General Maintenance:

1. Dust mop or sweep floor as necessary with a clean dust mop.
2. Damp mop using a neutral pH floor cleaner such as NEUTRAL CLEAN or NEUTRAPOWER.
3. High traffic areas can be quickly repaired between finish applications by using a mop on restorer like ARMOR-ACE, MAXICOAT or FLOOR FINISH 18. High traffic lanes can be recoated as needed.
4. Heavily soiled areas can be machine scrubbed using HD FLOOR CLEANER at the recommended dilutions and the appropriate floor scrubbing pad.

TIP: A sealer is not required, but if you have an old, worn or porous floor, consider applying HOLDOUT or FLOOR SEALER. One or two sealer coats are sufficient.

Application:

Ready-to-use

STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

PROMAX®