LAUNDRY CARE

Max Lift

NNED AND OCH HELD

Highly concentrated oxygen bleach \cdot Safe for colours

MAX LIFT is a concentrated liquid oxygen bleach for our closed-loop laundry chemical dispensing system. MAX LIFT is effective in removing stains from coloured fabrics that chlorine bleach cannot be used on. As well as preventing fabric discolouration from iron deposits, MAX LIFT is safe to use on almost all types of fabrics, white or coloured. Over time MAX LIFT breaks down to water and oxygen which makes it very environmentally friendly.

• Contains hydrogen peroxide

- Effective stain remover
- Longer shelf life than chlorinated bleach
- Quickly disperses throughout entire wash compartment

APPLICATIONS

Commercial laundry dilution system



TECHNICAL DATA

Appearance: clear liquid Colour: colorless Foam: none Odour: mild pH: 2.0-4.0

Packaging size 18.9L Packaging codes 1200640-18.9





DIRECTIONS

MAX LIFT is designed to be dispensed directly from the shipping container by your liquid laundry injection system.

Optimal bleaching conditions are: pH (wash) - 10.8 to 11.2 Time - 10 to 12 minutes Temperature - 76 to 82°C (170 to 180°F) Concentration - 15 to 60 ml (0.5-2 oz) per 45 kg load

NOTE: Test the fabric for colourfastness before use. Use a cotton swab to dot MAX LIFT on an inconspicuous spot on the garment, allow spot to dry completely. If you see any changes in the colour or transfer of colour from the garment to the swab, do not use MAX LIFT on this fabric.

FOR USE IN FOOD PLANTS: All food should be removed or covered prior to use and food contact surfaces are to be thoroughly rinsed with potable water so there will be no contamination of food as a result of its use.

STORAGE

Store locked up. Store in a dry, cool, well-ventilated place. Keep container tightly closed.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

PROMAX®