

SECTION 1: Identification

1.1. Product identifier

Trade name : PROMAX HY-BUILT
Product code : 1200478

1.2. Recommended use and restrictions on use

Recommended use : Laundry powder detergent
Restrictions on use : Industrial and Institutional use only

1.3. Supplier

Project Clean Inc.
12 James St N, Suite 201A
Hamilton, Ontario L8R 2J9
T 1 800 663 9925
regulatory@projectclean.com - www.projectclean.ca

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Canada	CHEMTREC Chemical Emergency	www.chemtrec.com	1 800 424 9300	24hr/day 7days/week within USA and Canada
Canada	CANUTEC Transportation Emergency	www.canutec.com	1 888 226 8832 *666 on a cell phone	24hr/day 7days/week within USA and Canada

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Corrosive to metals, Category 1	H290	May be corrosive to metals.
Skin corrosion/irritation, Category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation.

Full text of H-statements: see section 16


PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA) : 

Signal word (GHS CA) : Danger

Hazard statements (GHS CA) : H290 - May be corrosive to metals.
H314 - Causes severe skin burns and eye damage.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.

Precautionary statements (GHS CA) : P234 - Keep only in original container.
P260 - Do not breathe dust, mist, vapours, or spray.
P261 - Avoid breathing dust, mist, vapours, or spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on the product SDS).
P363 - Wash contaminated clothing before reuse.
P390 - Absorb spillage to prevent material damage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P406 - Store in corrosive resistant container with a resistant inner liner.
P501 - Dispose of contents and or container to hazardous or special waste collection point, in accordance with local, regional, national and or international regulation.

2.3. Other hazards

No additional information available

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	% w/w
Sodium metasilicate	silicic acid (H ₂ -SiO ₃), disodium salt	CAS-No.: 6834-92-0	45 – 70
Pentasodium triphosphate	Sodium tripolyphosphate	CAS-No.: 7758-29-4	5 – 10
C9-11, Ethoxylated Alcohol	(C9-C11) Alkyl alcohol, ethoxylate	CAS-No.: 68439-46-3	5 – 10
Sodium carbonate	Sodium carbonate, anhydrous	CAS-No.: 497-19-8	3 – 7
alcohols, C12-13, ethoxylated	alcohols, C12-13, ethoxylated	CAS-No.: 66455-14-9	1 – 5

**The exact concentrations have been withheld as a trade secret. Les concentrations exactes ont été retenues en tant que secret commercial.*

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water or shower. Take off immediately all contaminated clothing. Call a physician immediately.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.
- First-aid measures general : Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Burns.
- Symptoms/effects after eye contact : Serious damage to eyes.
- Symptoms/effects after ingestion : Burns.
- Chronic symptoms : No effects known.

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Expected Symptoms/Effects, Acute and Delayed : May cause dermatitis, eye irritation, corneal oedema and chemical burns. May cause skin irritation, dermatitis, or skin burns. Respiratory or skin sensitisation. Irritating to the digestive tract. May cause burns.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust, mist, vapours, or spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe dust, mist, vapours, or spray. Wear personal protective equipment.

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Incompatible products : Strong acids.

Incompatible materials : Metals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Materials for protective clothing:
Nitrile rubber/PVC
Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: White powder or lumps.
Colour	: White
Odour	: No added fragrance
Odour threshold	: No data available
pH	: No data available
pH solution	: 3,1 (12,5 – 13,5) %
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Initial boiling point and boiling range	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Upper and lower flammability or explosive limit	: No data available, Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20°C	: Not applicable.
Relative density	: 1 – 1,05
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: Not applicable
Explosive properties	: Not explosive.
Explosive limits	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: metals.

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time: : No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

PROMAX HY-BUILT	
LD50 oral rat	17803,6 mg/kg
LC50 Inhalation - Rat	45,2 mg/l/4h
ATE CA (oral)	17803,6 mg/kg bodyweight
ATE CA (vapours)	45,2 mg/l/4h
ATE CA (dust,mist)	45,2 mg/l/4h
Sodium metasilicate (6834-92-0)	
LD50 oral rat	1152 – 1349 mg/kg bodyweight (Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rat	> 5000 mg/kg bodyweight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2,06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
Pentasodium triphosphate (7758-29-4)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 4640 mg/kg bodyweight Animal: rabbit
LC50 Inhalation - Rat	> 0,39 mg/l Animal: rat, Guideline: EPA OPP 81-3 (Acute inhalation toxicity)
Sodium carbonate (497-19-8)	
LD50 oral rat	2800 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg (16 CFR 1500.40, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	2,3 mg/l (2 h, Rat, Male, Experimental value, Inhalation (aerosol), 10 day(s))
LC50 Inhalation - Rat (Dust/Mist)	1,2 mg/l Source: SIDS

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

C9-11, Ethoxylated Alcohol (68439-46-3)	
LD50 oral rat	1378 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)
ATE CA (oral)	1378 mg/kg bodyweight

alcohols, C12-13, ethoxylated (66455-14-9)	
LD50 oral rat	13627 – 14865 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Skin)
LC50 Inhalation - Rat	> 1,6 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, (maximum achievable concentration), Inhalation (aerosol), 14 day(s))
ATE CA (oral)	13627 mg/kg bodyweight
ATE CA (dust,mist)	1,5 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause respiratory irritation.

Sodium metasilicate (6834-92-0)	
STOT-single exposure	May cause respiratory irritation.

Pentasodium triphosphate (7758-29-4)	
STOT-single exposure	May cause drowsiness or dizziness.

Sodium carbonate (497-19-8)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Sodium metasilicate (6834-92-0)	
NOAEL (oral, rat, 90 days)	227 – 237 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard : Not classified

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

PROMAX HY-BUILT	
Viscosity, kinematic	Not applicable

Likely routes of exposure	: Skin and eyes contact. Inhalation. Ingestion.
Expected Symptoms/Effects, Acute and Delayed	: May cause dermatitis, eye irritation, corneal oedema and chemical burns. May cause skin irritation, dermatitis, or skin burns. Respiratory or skin sensitisation. Irritating to the digestive tract. May cause burns.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.
Chronic symptoms	: No effects known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Before neutralisation, the product may represent a danger to aquatic organisms.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Partition coefficient n-octanol/water (Log Pow)	No data available

Sodium metasilicate (6834-92-0)	
LC50 - Fish [1]	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [1]	207 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
Partition coefficient n-octanol/water (Log Pow)	-5,65
Pentasodium triphosphate (7758-29-4)	
LC50 - Fish [1]	590 mg/l Source: ECOTOX
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
Partition coefficient n-octanol/water (Log Pow)	-2,71 Source: Ecological Structure Activity Relationships
Sodium carbonate (497-19-8)	
EC50 96h - Algae [1]	242 mg/l Source: ECOTOX

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

alcohols, C12-13, ethoxylated (66455-14-9)	
LC50 - Fish [1]	0,96 mg/l (EPA OTS 797.1400, 96 h, Pimephales promelas, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	0,46 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, GLP)
EC50 96h - Algae [1]	0,22 mg/l (EPA OTS 797.1050, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF - Fish [1]	12,7 – 232,5 (72 h, Pimephales promelas, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	4,66 (Calculated, 25 °C)

12.2. Persistence and degradability

Persistence and degradability Contains readily biodegradable component(s).

Sodium metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
Sodium carbonate (497-19-8)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
C9-11, Ethoxylated Alcohol (68439-46-3)	
Persistence and degradability	Readily biodegradable in water.
alcohols, C12-13, ethoxylated (66455-14-9)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

Bioaccumulative potential Not established.

Partition coefficient n-octanol/water (Log Pow) No data available

Sodium metasilicate (6834-92-0)	
Bioaccumulative potential	Not bioaccumulative.

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Sodium metasilicate (6834-92-0)	
Partition coefficient n-octanol/water (Log Pow)	-5,65
Pentasodium triphosphate (7758-29-4)	
Partition coefficient n-octanol/water (Log Pow)	-2,71 Source: Ecological Structure Activity Relationships
Sodium carbonate (497-19-8)	
Bioaccumulative potential	Not bioaccumulative.
Partition coefficient n-octanol/water (Log Pow)	-6,19 Source: Quantitative Structure Activity Relation
C9-11, Ethoxylated Alcohol (68439-46-3)	
Bioaccumulative potential	No bioaccumulation data available.
alcohols, C12-13, ethoxylated (66455-14-9)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	12,7 - 232,5 (72 h, Pimephales promelas, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	4,66 (Calculated, 25 °C)

12.4. Mobility in soil

Ecology - soil No (test) data on mobility of the substance available.

Partition coefficient n-octanol/water (Log Pow) No data available

Sodium metasilicate (6834-92-0)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.
Partition coefficient n-octanol/water (Log Pow)	-5,65
Pentasodium triphosphate (7758-29-4)	
Partition coefficient n-octanol/water (Log Pow)	-2,71 Source: Ecological Structure Activity Relationships
Sodium carbonate (497-19-8)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.
Partition coefficient n-octanol/water (Log Pow)	-6,19 Source: Quantitative Structure Activity Relation

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

alcohols, C12-13, ethoxylated (66455-14-9)	
Surface tension	28 mN/m (30 °C, 1.01 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	Low potential for adsorption in soil.
Partition coefficient n-octanol/water (Log Pow)	4,66 (Calculated, 25 °C)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents and or container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Non-refillable container. Do not reuse or refill this container. Offer for recycling, if available or puncture and dispose of in a sanitary landfill.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No. (TDG) : UN3253

14.2. UN proper shipping name

Proper Shipping Name (TDG) : DISODIUM TRIOXOSILICATE


Transport document description (TDG) : UN3253 DISODIUM TRIOXOSILICATE, 8, III

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : 8

Hazard labels (TDG) : 8



14.4. Packing group

Packing group (TDG) : III

14.5. Environmental hazards

Other information : No supplementary information available.

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.6. Special precautions for user

TDG

UN-No. (TDG)	:	UN3253
Explosive Limit and Limited Quantity Index	:	5 kg
Excepted quantities (TDG)	:	E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	:	25 kg
Emergency Response Guide (ERG) Number	:	154

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

Sodium metasilicate (6834-92-0)

Listed on the Canadian DSL (Domestic Substances List)

Pentasodium triphosphate (7758-29-4)

Listed on the Canadian DSL (Domestic Substances List)

Sodium carbonate (497-19-8)

Listed on the Canadian DSL (Domestic Substances List)

C9-11, Ethoxylated Alcohol (68439-46-3)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Sodium metasilicate (6834-92-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Pentasodium triphosphate (7758-29-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

PROMAX HY-BUILT

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Sodium carbonate (497-19-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

C9-11, Ethoxylated Alcohol (68439-46-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

Issue date : 12.01.2023

Full text of H-statements:

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. Project Clean Inc. will accept no liability for damages or loss incurred from the improper handling and use of this product.

The information provided in the Safety Data Sheet has been obtained from current sources and is believed to be reliable.