

INDUSTRIAL

Oxy-Slam

Power degreaser & deodorizer • Contains Hydrogen Peroxide



Oxy-Slam is a powerful d-limonene degreaser with the extra boost of hydrogen peroxide. Oxy-Slam is designed for industrial and food plant applications.

- Biodegradable ingredients
- Food Safe
- Citrus scented
- Removes oil and grease
- Contains d-limonene

APPLICATIONS

Food processing

Floors

Waste areas, bins and chutes

Engine degreasing

Showers

Commercial laundry



TECHNICAL DATA

Appearance: clear liquid

Colour: colourless

Foam: moderate

Odour: citrus

pH: 1.5-2.5

Packaging size

4 x 3.78L

Packaging codes

1300835-4cs



PROMAX®

DIRECTIONS

Do NOT mix with acid, alkaline or ammonia.

Food Processing Areas: Dilute 30 ml of OXY-SLAM per litre of water (4 oz/gal) (1:32) through foaming units or sprayers. Rinse well with water.

Floors: Dilute 15 ml of OXY-SLAM per litre of water (2 oz/gallon) (1:64).

Laundry Applications: As a color-safe laundry brightener, dilute 85 ml (3 oz) per 22 kg (50 lb) of dry weight of laundry. As a grease spotter, apply OXY-SLAM directly to stains and launder.

Industrial Applications: Dilute 50 ml of OXY-SLAM per litre of water (6 oz/gal) (1:20) for general degreasing and oil removal. Dilute 200 ml of OXY-SLAM per litre of water (25 oz/gal) (1:5) for engine degreasing. Spray on. Let stand 5 minutes, then hose down with water.

Garbage areas, Trucks and Containers: Dilute 65 ml of OXY-SLAM per litre of water (8 oz/gal) (1:15) to clean and deodorize garbage trucks, chutes and metal garbage containers.

Extreme Build-up: Spray on undiluted. Let stand 3-5 minutes. Rinse with hot water or steam.

Showers: Dilute 100 ml of OXY-SLAM per litre of water (13 oz/gal) (1:10). Let stand and rinse.

FOR USE IN FOOD PLANTS: All food should be removed or covered prior to use and food contact surfaces are to be thoroughly rinsed with potable water so there will be no contamination of food as a result of its use.

Application:

Food processing areas	1:32
Floors	1:64
Laundry applications	85ml / 22kg load
Industrial applications	1:20-1:5
Garbage areas, trucks and containers	1:15
Extreme buildup	Full strength
Showers	1:10

STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals. Store locked up. Store in a cool, dry, well-ventilated place. Do not store in aluminum, copper, copper alloys and galvanized containers.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

PROMAX®