

KITCHEN CARE

Scale Away

Scale & rust remover · Inhibited hydrochloric acid

SCALE AWAY is an acid cleaner designed to remove hard water scale build-up on most steel, stainless steel, glass, fiberglass, plastic, concrete and ceramic surfaces. SCALE AWAY can also remove the unsightly deposits from soap scum, mineral deposits and rust build-up on many surfaces including toilet bowls, urinals, shower stalls, and sinks. SCALE AWAY contains special inhibitors, which prevent corrosion to steel and stainless-steel metals while allowing the scale deposits to be dissolved.

- Prevents corrosion to steel & stainless-steel metals
- Dissolves scale deposits

APPLICATIONS

Glassware
Silverware
Dishware

Cookware
Appliances
Pots & Pans



TECHNICAL DATA

Appearance: clear liquid
Colour: colourless
Foam: low
Odour: mild acidic
pH: 1.0-2.0

Packaging size
4 x 3.78 L

Packaging codes
1401210-4cs

PROMAX®

DIRECTIONS

Heavy deposits: dilute SCALE AWAY at 1000 ml per litre of water (128 oz /gallon) (1:1) and scrub the surface with an acid-resistant brush. Rinse thoroughly with water and repeat if necessary.

Light to medium scale deposits: Dilute SCALE AWAY at 250 ml per litre of water (20 oz/gallon) (1:4) and apply solution with an acid-resistant brush or swab. When using SCALE AWAY on cement, rinse and neutralize with a solution of Soda Ash.

Dishwashers: Add 250mL SCALE AWAY directly to dish machine and run one wash and rinse cycle to maintain scale-free surfaces. If heavy scale is present, use up to 500mL per cycle to descale. If deposit is heavy, scrub surface with a brush.

Wipe up any excess solution and discard. Rinse thoroughly with water. In difficult cases, repeat the application if necessary.

FOR USE IN FOOD PLANTS: All food should be removed or covered prior to use and food contact surfaces are to be thoroughly rinsed with potable water so there will be no contamination of food as a result of its use.

Application:

Heavy deposits	1:1
Light to medium scale deposits	1:4
Dishwashers	250-500ml per cycle

STORAGE

Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up. Store in a dry, cool, well-ventilated place.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

PROMAX®