

## ODOUR CONTROL

# Aquabac

Bacterial based cleaner · Highly concentrated

AQUABAC is a living, non-pathogenic bacterial treatment, which breaks down and liquefies solids such as fats, proteins, carbohydrates and grease. The carefully cultivated bacteria are the active components behind AQUABAC's ability to quickly break down waste and eliminate odours. With over 200 billion spores per gallon, the synergized blend of multi-strain bacteria in AQUABAC will remain 100% active until their work is done, at which time they begin rebuilding their colonies to replace the loss and the cycle is repeated, resulting in a successful ongoing drain or grease trap maintenance program. Ideal for high traffic facilities such as hospitals, nursing homes and schools.

- Deodorizes
- Breaks down organic waste
- Over 200 million spores per gallon
- Regenerating population

## APPLICATIONS

Drains  
Waste containers  
Washrooms  
Grease traps  
Commercial kitchens

Waste sluices and conduits  
Waste plants  
Holding ponds  
Portable toilets



## TECHNICAL DATA

**Appearance:** opaque liquid

**Colour:** white

**Foam:** low

**Odour:** fresh scent

**pH:** 6.5-7.5

**Packaging size**

4x3.78L

**Packaging codes**

1300075-4cs



# PROMAX®

## DIRECTIONS

AGITATE CONTAINER BEFORE USE.

**General Odour Control: To eliminate odours caused by spoiled foods, decomposed animals, vomit, incontinence, animal wastes, garbage cans, waste receptacles, locker rooms and carpeted areas:** Spray product directly on malodor and allow bacterial action in AQUABAC to ingest the material. Keep moist for at least 30 minutes.

**Drain Lines & Drainpipes:** Dose 2-4 times weekly. Dilute 120 ml (4 oz.) of AQUABAC for every 5 cm (2 in.) of pipe size directly into drain. Begin at the lowest floor and go up one floor each day. When top floor is treated continue to dose from top floor only.

**Grease Traps:** For traps less than 568 L (150 gal) capacity, add 120-150 ml (4-6 oz.) of product daily, by pouring or pumping in a pipeline closest to the trap. This should be done at night or when traps are used the least. Flush down with a cup of lukewarm water. For grease traps larger than 568 L, add 240-300 ml (8-10 oz.) daily using the same procedure.

**Digesting Organic Waste and Carpet Deodorizing: Manual:** Vacuum carpet thoroughly after spot cleaning stain. Dilute 60-120 ml (2-3 oz.) of AQUABAC per litre of water (1:16-1:11). Apply with a pump or hand sprayer. Keep moist for at least 30 minutes. Repeat if odour persists.

**Carpet Cleaning Equipment:** Dilute 60 ml (2 oz.) of AQUABAC to every litre of mixed cleaner (1:16).

**Municipal Waste Processing Plants and Sewage Systems:** Use 3 gallons per million gallons of flow per day (3 ppm) for 3 to 6 days, then use 1 gallon per million for regular maintenance (1 ppm).

**Food Processing and Industrial Manufacturing Plants:** Treat ponds, lagoons and retention areas with above dosage rates.

**Septic Tanks:** Dilute 475 ml per 710 litre capacity (1:1500) for initial treatment. Thereafter, use 240 ml (1:3000) per week. Pour directly into toilet and flush. If septic tank is clogged and odorous, add 3.78 litres (1 gal) of product directly to tank through manhole.

**Porta-Toilets:** Add 3.78 litres (1 gal) directly and cover solids with water to aid digestion. Each time toilet is pumped, start treatment again with 3.78 litres of AQUABAC.

**Recreational Vehicles & Boats:** Dilute 16 ml per litre of water (1:64) in hold tank. Thereafter, use 8 ml per litre (1:128) as needed. For use at a dumping station, use 1 litre per 50 litre of tank capacity (1:50). Then use 475 ml per week for maintenance (1:100).

**NOTE: This product is not intended for use as a space spray.**

**FOR USE IN FOOD PLANTS:** All food should be removed or covered prior to use and food contact surfaces are to be thoroughly rinsed with potable water so there will be no contamination of food as a result of its use.

---

## STORAGE

Keep in a cool, well-ventilated place away from heat. Protect from sunlight. Always store product in container of same material as original container.

## SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at [projectclean.com](http://projectclean.com) or by calling 1-800-663-9925. Improper use may result in damage or injury.

**PROMAX®**