

CLEANERS & DEGREASERS

Knock it off!

Dual safe-acid descaler · Low foaming

KNOCK IT OFF! contains two types of acids that dissolve difficult to remove scale containing magnesium, calcium and silicates among others. KNOCK IT OFF! is corrosive to aluminum only. Non-corrosive to skin and steel.

- ECOLOGO® Certified
- Non-irritant to skin
- Excellent aquatic toxicity profile
- Dissolves difficult stains
- Removes all types of mineral scale
- Food Safe

APPLICATIONS

Washrooms
 Commercial Kitchens
 Cisterns
 Commercial Beverage Production
 Industrial Machinery
 Dip Tanks



TECHNICAL DATA

Appearance: clear liquid
Colour: colourless
Foam: low
Odour: no fragrance
pH: 1.0-1.6

Packaging size
 4 x 3.78L

Packaging codes
 1300680-4cs



PROMAX®

DIRECTIONS

Preparation: Use unheated tap water for dilution.

Heavy duty scale removal: Dilute 1 part KNOCK IT OFF! with 1-part cold tap water (1:1) or use full strength.

Medium duty scale removal: Dilute 1 part KNOCK IT OFF! with 4 parts cold tap water (1:4).

Light duty scale removal: Dilute 1 part KNOCK IT OFF! with 8 parts cold tap water (1:8).

1. Rinse off all loose scale with pressure sprayer and determine level of scaling.
2. Fill or submerge the equipment slowly into recommended product dilution. Ensure the exposed tubing and walls have been in contact with the solution.
3. Leave the descaling solution in contact for 30 minutes to 4 hours and periodically check scale removal by lightly scrubbing with a bristle brush on all contact surfaces. The amount of contact time will vary depending on the level of scale residues.
4. Spent solution can be reused or poured down the drain with lots of water. If reusing the dilution liquid, start the process with the most concentrated dilution and the most scaled equipment.
5. Rinse out equipment parts thoroughly 3-5 times with fresh water. Check the final rinse water with pH test strip to match incoming water pH (should be around pH 6). A separate neutralization step is not required.

NOTE: DO NOT let KNOCK IT OFF! dry on metal surfaces. Rinse surfaces well after descaling.

FOR USE IN FOOD PLANTS: All food should be removed or covered prior to use and food contact surfaces are to be thoroughly rinsed with potable water so there will be no contamination of food as a result of its use.

Application:

Heavy duty scale removal	Full strength
Medium duty scale removal	1:4
Light duty scale removal	1:8

STORAGE

Keep in a cool, well-ventilated place away from heat. Store in corrosive resistant container with a resistant inner liner. Keep only in original container.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

PROMAX®