

FLOOR CARE

Sheergloss

High solids floor finish · Fast drying

SHEERGLOSS is a high solids, fast-drying premium floor finish producing a high gloss durable coating that resists scratches, scuffs and blackmarks. Designed to provide maximum gloss and durability, it extends the life and improves the appearance of floors. SHEERGLOSS has an excellent burnish response and can be used with or without a sealer.

- High gloss with or without burnishing
- Blackmark resistance
- Superior detergent and oil resistance
- Long lasting burnishable gloss
- Smooth leveling
- No yellowing or discoloration

APPLICATIONS

Resilient flooring

Terrazzo

Concrete



TECHNICAL DATA

Appearance: liquid

Colour: opaque white

Foam: none

Odour: Mild, no added fragrance

pH: 8.5-9.0

Packaging size

4 x 3.78L
18.9L pail

Packaging codes

1300990-4cs
1300990-18.9



PROMAX®

DIRECTIONS

Covers up to 3000 square feet per gallon minimum depending on application method and porosity of floor.

General Application:

1. Completely strip old floor finish with a floor finish remover such as FINISH REMOVER or #1 REMOVER
2. Remove the stripping solution and rinse floor with a neutral pH cleaner such as NEUTRAPOWER and NEUTRAL CLEAN or follow with two to three clear water rinses. Allow to dry.
3. Apply SHEERGLOSS in a uniform, thin coat with either fine string mop or finish applicator. Allow finish to dry thoroughly for 20- 30 minutes depending upon the surrounding air flow, temperature and humidity. Do not apply additional coats until surface is dry to the touch.
4. Apply additional coats following the same techniques. Applying four to five coats is optimum. More may be required if you have an un-sealed, porous floor or need a good base to propane burnish.

General Maintenance:

1. Dust mop or sweep floor as necessary with a clean dust mop.
2. Damp mop using a neutral pH floor cleaner such as NEUTRAL CLEAN or NEUTRAPOWER
3. High traffic areas can be quickly repaired between finish applications by using a mop on restorer like ARMOR-ACE, MAXICOAT or FLOOR FINISH 18. High traffic lanes can be recoated as needed.
4. Heavily soiled areas can be machine scrubbed using HD FLOOR CLEAN at the recommended dilutions and the appropriate floor scrubbing pad.
5. Spray buff or burnish as desired.

TIP: A sealer is not required, but if you have an old, worn or fairly porous floor, consider applying HOLDOUT or FLOOR SEALER. One or two sealer coats are sufficient.

Application:

Ready-to-use

STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

PROMAX®