

SECTION 1: Identification

1.1. Identification

Product name : MAXICOAT
Product code : U130695

1.2. Recommended use and restrictions on use

Recommended use : Floor finish cleaner restorer
Restrictions on use : Industrial and Institutional use only

1.3. Supplier

Project Clean Inc.
2330 Industrial Parkway SW
Dyersville, IA 52040
T 1 800 663 9925
www.projectclean.com

1.4. Emergency telephone number

Country	Organization/Company	Address	Emergency number	Comment
USA	CHEMTREC Chemical Emergency	www.chemtrec.com	1 800 424 9300	24hr/day 7days/week within USA and Canada
USA	CANUTEC Transportation Emergencies	www.canutec.com	1 888 226 8832 *666 on a cell phone	24hr/day 7days/week within USA and Canada

SECTION 2: Hazard(s) identification


2.1. Classification of the substance or mixture

GHS US classification

Skin sensitization, Category 1 H317 May cause an allergic skin reaction
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) : 

Signal word (GHS US) : Warning
Hazard statements (GHS US) : H317 - May cause an allergic skin reaction

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US) : P261 - Avoid breathing fume/mist/vapours/spray.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing.
P302+P352 - If on skin: Wash with plenty of water.
P321 - Specific treatment (see supplemental first aid instruction in Section 4 or on the product SDS).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P363 - Wash contaminated clothing before reuse.
P501 - Dispose of contents and or container to hazardous or special waste collection point, in accordance with local, regional, national and or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Glycol ether DPM	CAS-No.: 34590-94-8	7 - 13
Tributoxy ethyl phosphate	CAS-No.: 78-51-3	1 - 5
Zinc ammonia carbonate complex	CAS-No.: 38714-47-5	0.1 - 1

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice or attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (acute and delayed)

Expected Symptoms/Effects, Acute and Delayed	:	May produce an allergic reaction.
Symptoms/effects after skin contact	:	May cause an allergic skin reaction.
Chronic symptoms	:	Dry skin. Cracking of the skin.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin. Do not handle until all safety precautions have been read and understood. Clean up any spills as soon as possible, using an absorbent material to collect it.

6.1.1. For non-emergency personnel

Protective equipment : Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Emergency procedures : Ventilate spillage area. Avoid breathing fume, mist, vapours, or spray. Avoid contact with skin.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls or personal protection".

Emergency procedures : Ventilate area. Evacuate unnecessary personnel. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Reuse if possible. Otherwise dispose recovered material in accordance with all local, Provincial or Federal regulations.

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid breathing fume, mist, vapours, or spray. Wear personal protective equipment. Avoid contact with skin.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

MAXICOAT	
No additional information available	
Tributoxy ethyl phosphate (78-51-3)	
No additional information available	
Glycol ether DPM (34590-94-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
ACGIH OEL TWA	50 ppm
Remark (ACGIH)	TLV® Basis: Liver & CNS eff
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Glycol ether DPM (34590-94-8)	
OSHA PEL TWA	600 mg/m ³
	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Zinc ammonia carbonate complex (38714-47-5)	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Materials for protective clothing:
Nitrile rubber/PVC
Hand protection:
Protective gloves against chemicals (EN 374)
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Milky white liquid.
Color	: milky
Odor	: Slight ammonia odor
Odor threshold	: No data available
pH	: 7 – 8

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: Not applicable
Freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: ≥ 100 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Upper and lower flammability or explosive limit	: No data available, Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1 – 1.05
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not self-igniting
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: Thin like water
Explosion limits	: No data available
Explosive properties	: Product is not explosive.
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

MAXICOAT	
LD50 oral rat	≥ 35335 mg/kg
LD50 dermal rat	54726.4 mg/kg
LC50 Inhalation - Rat	74.627 mg/l/4h
ATE US (dermal)	54726.4 mg/kg body weight
ATE US (vapors)	74.627 mg/l/4h
ATE US (dust, mist)	74.627 mg/l/4h
Tributoxy ethyl phosphate (78-51-3)	
LD50 oral rat	> 5000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 2040 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 6.4 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol))
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Glycol ether DPM (34590-94-8)	
LD50 oral rat	> 5000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 19020 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	9510 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Glycol ether DPM (34590-94-8)	
LC50 Inhalation - Rat	> 3000 mg/m ³ Source: ECHA
ATE US (dermal)	9510 mg/kg body weight
Zinc ammonia carbonate complex (38714-47-5)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity), Guideline: other:
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
Tributoxy ethyl phosphate (78-51-3)	
STOT-single exposure	May cause respiratory irritation.
Glycol ether DPM (34590-94-8)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Glycol ether DPM (34590-94-8)	
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: other:
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Likely routes of exposure	: Skin and eye contact. Inhalation.
Expected Symptoms/Effects, Acute and Delayed	: May produce an allergic reaction.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Chronic symptoms	: Dry skin. Cracking of the skin.

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Tributoxy ethyl phosphate (78-51-3)	
LC50 - Fish [1]	11.2 mg/l Source: International Uniform Chemical Information Database
EC50 - Crustacea [1]	75 mg/l Source: International Uniform Chemical Information Database
Glycol ether DPM (34590-94-8)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata, Static system, Fresh water, Experimental value, GLP)
EC50 - Other aquatic organisms [1]	1930 mg/l Test organisms (species): other aquatic crustacea:
ErC50 algae	> 969 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
LOEC (chronic)	0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'
NOEC (chronic)	≥ 0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'

12.2. Persistence and degradability

MAXICOAT

Persistence and degradability The polymers are not biodegradable, but they would be removed in biological wastewater treatment plants by adsorption to biosolids. No bioconcentration of the polymeric component is expected.

Tributoxy ethyl phosphate (78-51-3)	
Persistence and degradability	Inherently biodegradable.
Chemical oxygen demand (COD)	1.839 g O ₂ /g substance
Glycol ether DPM (34590-94-8)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance
ThOD	2.06 g O ₂ /g substance

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

MAXICOAT

Partition coefficient n-octanol/water (Log Kow) No data available

Bioaccumulative potential Not established.

Tributoxy ethyl phosphate (78-51-3)	
Partition coefficient n-octanol/water (Log Pow)	3.75 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Glycol ether DPM (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.004 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Zinc ammonia carbonate complex (38714-47-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.46 Source: ECHA

12.4. Mobility in soil

MAXICOAT

Ecology - soil No (test) data on mobility of the substance available.

Tributoxy ethyl phosphate (78-51-3)	
Surface tension	32.7 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Ecology - soil	No (test) data on mobility of the substance available.
Glycol ether DPM (34590-94-8)	
Surface tension	68.7 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil. Not toxic to plants.

12.5. Other adverse effects

No additional information available

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

- Waste treatment methods : Dispose of contents and or container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Reuse if possible. Otherwise dispose recovered material in accordance with all local, State or Federal regulations.
- Ecological waste information : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Zinc ammonia carbonate complex	CAS-No. 38714-47-5	0.1 – 1%
--------------------------------	--------------------	----------

MAXICOAT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 04/15/2023


Full text of hazard classes and H-statements

H317	May cause an allergic skin reaction
------	-------------------------------------

NFPA health : 1 - Materials that, under emergency conditions, can cause hazard significant irritation.

NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. Project Clean Inc. will accept no liability for damages or loss incurred from the improper handling and use of this product.

The information provided in the Safety Data Sheet has been obtained from current sources and is believed to be reliable.