

FLOOR CARE

Satin Finish

Matte floor finish · Citrus scented

SATIN FINISH levels easily and dries quickly to a durable matte gloss film that provides outstanding resistance to marks, scuffing, maintenance cleaning and heavy traffic. It is ideal for facilities requiring a durable non wet look finish. Formulated with a high-performance blend of tough, hard and flexible polymers, SATIN FINISH creates an extremely durable coating extending the life of the finish, requiring less stripping and recoating. SATIN FINISH can be used on most types of resilient flooring such as linoleum, marmoleum, vinyl sheet and vinyl composite tile. SATIN FINISH is highly recommended for healthcare and senior facilities.

- 16% solid
- Matte finish
- Ease of application
- Non-yellowing
- Low maintenance
- Superior detergent resistance

APPLICATIONS

Resilient flooring
 Linoleum
 Sheet vinyl
 Marmoleum

Quarry tile
 Terrazzo
 Concrete



TECHNICAL DATA

Appearance: liquid
Color: opaque white
Foam: none
Odor: Mild, no added fragrance
pH: 8.5-9.0

Packaging size
 4 x 1 US Gallon
 5 Gallon Pail

Packaging codes
 U130945-4c22
 U130945-5gal



DIRECTIONS

Covers up to 3000 square feet per gallon minimum depending on application method and porosity of floor.
AGITATE CONTAINER BEFORE USE.

General Application:

1. Completely strip all old wax or floor finish with a floor finish remover like FINISH REMOVER or #1 REMOVER.
2. Remove the stripping solution and follow with one or two clear-water rinses. Allow floor to dry.
3. For extra durability, two coats of FLOOR SEALER or HOLDOUT can be applied but is not required.
4. Apply SATIN FINISH in a uniform, thin coat. Let dry thoroughly for 20 to 30 minutes depending upon the surrounding air flow, temperature and humidity. Do not apply additional coats until surface is dry to the touch. Apply additional coats following the same techniques. Applying three to five coats is optimum.

General Maintenance:

1. Dust mop or sweep floor as necessary with a clean dust mop.
2. Damp mop using a neutral pH floor cleaner such as NEUTRAL CLEAN or NEUTRAPOWER.
3. High traffic areas can be quickly repaired between finish applications by scrubbing area with a solution of multi-purpose cleaner such as ALL CLEAN as per label direction and recoating with SATIN FINISH as needed.
4. Heavily soiled areas can be machine scrubbed using HD FLOOR CLEAN or ALL DEGREASE & CLEAN at the recommended dilutions and the appropriate floor scrubbing pad.

NOTE: To maintain matte finish, do not buff or burnish.

Application:

Ready-to-use

STORAGE

Keep from freezing. Store upright in closed container at room temperature away from children. Do not mix with any other chemicals.

SAFE HANDLING

Before usage, ensure employees read and understand the product labels and Safety Data Sheet. Directions for use can be found on the label and the TDS. Employees can find hazard warnings, precautionary statements and first aid procedures on the SDS sheets. SDS are available online at projectclean.com or by calling 1-800-663-9925. Improper use may result in damage or injury.

PROMAX®